

# AHLSTAR APP pump, the perfect solution for corrosive liquid

In the phosphoric fertilizer manufacturing process, fluorosilicic acid ( $H_2SiF_6$ ) is a by-product. It is the end product of phosphoric acid production (reaction). The process requires pumping at different concentrations. The customer uses fluorosilicic acid in different departments such as fluorine salts manufacturing.



AHLSTAR APP11-50 pump

## The Sulzer difference

The combination of correct material selection, seal selection and seal arrangement gave a perfect result and a satisfied customer.

## The challenge

The biggest challenge in pumping is strong fluorosilicic acid (up to 20%). At this concentration, it is very corrosive. In addition, the liquid contains very fine solids (SiO<sub>2</sub> gel). This combination is a challenge for the material selection. The material should be both corrosion resistant and abrasion resistant.

#### The solution

Avesta 654 SMO was proven to be the best material for this application. The elastomers for the seal should also be selected carefully, because they should withstand this liquid. The customer also required a reliable water supply system, so Thermosyphone AesSeal with a level switch was proposed.

#### **Customer benefits**

The selected pump features minimized lifecycle costs and improved process reliability.

# Pump data

Pump AHLSTAR APP11-50, ser. no 100092935,

double mechanical seal Burgmann

Material 4U
Capacity 70 m³/h
Head 50 m
Speed 3'000 rpm
Motor power 30 kW

# Process data

 $\begin{array}{lll} \mbox{Fluorosilicic acid $H_2SiF_6$ 20\%$} \\ \mbox{Temperature} & 30^{\circ}\mbox{C max} \\ \gamma & 1'180 \mbox{ kg/m}^{3} \\ \mbox{Solids} & 10 \mbox{ g/l (SiO}_2 \mbox{ gel)} \\ \mbox{Solids size} & 0.01 \mbox{ mm} \\ \end{array}$ 

### Contact

info\_fmmcpi@sulzer.com

#### www.sulzer.com